

FEATURES & SPECIFICATIONS | eDeliver 9 N2 Chassis Cab L4 H0 RWD 100kWh

Exterior

LED headlights	S	Power heated exterior mirrors	S
Front & rear fog lights	S	Removable front tow hook	S
Steel wheel 6.5Jx16	O	Rear trailer tow interface	S
Alloy wheel 6.5Jx16	S		

Interior & Comfort

Microfibre leather multifunctional steering wheel with heated steering wheel	S	Automatic air conditioner	S
Anti-glare interior mirror	S	12.3" touch screen with MP5 & USB & Bluetooth & CarPlay & Android Auto	S
Column-mounted shifter	S	IOV (Internet of vehicle)—Vehicle condition & Remote control	O
Heated front seats	S	4 speakers	S
LED front reading light	S	DAB	S
Power front windows (one click up & down)	S	Keyless start	S
Automatic windshield wiper	S	2 smart keys	S

Safety & Security

Tyre pressure monitoring system	S	Safety belt reminder	S
6 airbags (front,side,curtain) for driver & front passengers	S	Front radar	S

Driver Assistance

ESP+EBA+HHC	S	Blind spot information system & moving off information system	S
EPB	S	Speed limit information	S
Full-speed ACC	S	Driver monitor system	S
Automatic emergency braking system	S	Adjustable overspeed warning	S
Lane departure warning & lane keeping assist system	S		

FEATURES & SPECIFICATIONS | eDeliver 9 N2 Chassis Cab L4 H0 RWD 100kWh

For conversion			
105Ah 12V battery with battery guard	S	Reserved interface for tachograph	S
Bodybuilder plug	S		

TECHNICAL SPECIFICATIONS | eDeliver 9 N2 Chassis Cab L4 H0 RWD 100kWh

Dimensions & Capacities

Number of seats	3	Maximum permissible length (mm)	7092
Rear Wheels	Single	Maximum permissible width (mm)	2250
Overall length (mm)	6680	Maximum permissible height (mm)	3300
Overall width (mm)	2052	Ground clearance of the front axle (mm)	187
Overall height (mm)	2325	Ground clearance of the rear axle (mm)	147
Wheel base (mm)	4048	Ground clearance between axles (mm)	205

Weights & Payload

GVW (kg)	4250	Max axle lead: front/rear (kg)	1950/2760
CVW (kg)	2360	GTM (kg)	6000
Payload: GVW-CVW (kg)	1890	Towing capacity (Braked/Unbraked) (kg)	2000/750
GVW axle load: front/rear (kg)	1680~1765/ 2570~2485		

Battery & Charging

Battery capacity (kWh)	100	Battery thermal management & liquid cooling & liquid heating	S
Range WLTP combined (miles)*	121~173	11kw AC charger & EPTO (high voltage power take-off)**	S
Range WLTP city (miles)*	168~242	22kw AC charger & DCDC (low voltage power take-off)**	O
Energy consumption WLTP combined (kWh/62mph)*	38.7~54.5	Charging cable (11kw)	S
AC Charging time (5%~100%) (h)/ Charging power (kW) Three-Phase	10.5h/11kw (S) 5.9h/22kw (O)	V2L exterior	S
DC Charging time (10%~80%) (h)/ Charging power (kw)	47min/100kW		

Power & Driving & Steering

Driving wheel	RWD	Min turning diameter (m)	15.2±1
Rated power/Max power (kW)	70/170	Approach angle/departure angle (°)	18.8/18.6
Rated torque/Max torque (N.m)	170/330	Tyre	235/65R16
Max speed (mph)	56		

*Estimated range & energy consumption under EU WLTP test standard. Actual range & energy consumption varies with conditions such as temperature, operation of air conditioner, driving mode, route conditions, battery capacity loss and loading mass.

**When you choose 22kw AC charger & DCDC, 11kw AC charger & EPTO is not available. The available power of DCDC is 2.5kw. The available power of EPTO is 3.5kw for 88kWh models and 5.2kw for 100kWh modes.

